

# ATN-FBL

## Attenuation Optical Fiber



Coractive's attenuation optical fiber (ATN) products have been specifically designed to provide flat attenuation, from 1250 nm to 1620 nm. Wideband uniform attenuation ensures full compatibility with current and future DWDM, CATV and other telecom systems. The ATN-FBL has a wide attenuation range (<0.4 dB/cm) for manufacturing patchcord-type attenuators used in telecommunications.

## Features & Benefits

- Industry-standard fiber geometry – provides **high-precision core alignment** for more efficient fiber coupling
- Precise cladding diameter control – **perfect ferrule fit** reducing manufacturing costs & increasing production yield
- Tight attenuation tolerance – enables compatibility with DWDM network applications
- Full spectrum flat attenuation: from 1250 nm to 1620 nm
- Exceptional **batch-to-batch uniformity** – ensures a consistent and high-quality attenuator
- Wide attenuation range: from 0.005 to 0.4 dB/cm

## Applications

- Patchcord-type attenuators
- Telecom (DWDM, CATV)

## Specifications

### Optical

Core Numerical Aperture – Nominal (%)	0.14 ± 0.02
Attenuation Range* (dB/m)	0.005 - 0.4
Operating Wavelength (nm)	1250 - 1620
Attenuation Tolerance – Nominal (%)	7.5

### Geometrical & Mechanical

Core Diameter (µm)	7 ± 1
Cladding Diameter (µm)	125 ± 0.5
Core/Cladding Concentricity Error (µm)	< 0.8
Coating Diameter (µm)	245 ± 10
Proof Test (kpsi)	≥ 100

### Environmental

Operating Humidity (%)	5 - 85
Operating Temperature (C°)	0 - 70
Storage Humidity (%)	5 - 85
Storage Temperature (C°)	-40 - 85

ISO 9001:2015 certified quality system | RoHS and REACH compliant.

All specifications are subject to change without notice. Reference: 100-10-0268.R2

\* Not all attenuations are available within given range. Please contact your sale representative for more information.