

# SCF-UN-205/220-22

## Single-Clad Passive Fiber



Designed for the fiber coupling of high-power diode lasers, the SCF-UN-205/220-22 passive fiber features excellent properties and is compatible with industry standards. It is also used for manufacturing passive components such as pump combiners for high-power fiber lasers.

### Features & Benefits

---

- Compatible with industry-standard active fibers
- Low background losses
- Excellent geometrical properties

### Applications

---

- Passive component manufacturing
- Fiber coupling of high-power diode lasers
- Fiber lasers and amplifiers

### Related Products

---

- [SCF-UN-109/125-22](#)  
Single-clad passive fiber

### Specifications

---

#### Optical

Numerical Aperture - Core	0.22 ± 0.02
Background Loss @ 1200 nm (dB/km)	< 50

#### Geometrical & Mechanical

Core Diameter (µm)	205 ± 5
Cladding Diameter (µm)	220 ± 3
Core/Cladding Concentricity Error (µm)	> 3
Coating Diameter (µm)	320 ± 15
Proof Test (kpsi)	≥ 100

#### Environmental

Operating Humidity (%)	5 - 85
Operating Temperature (C°)	0 - 70
Storage Humidity (%)	5 - 85
Storage Temperature (C°)	-40 - 85

ISO 9001:2015 certified quality system | RoHS and REACH compliant.  
All specifications are subject to change without notice. Reference: 100-10-0935.R1